

MICROWAVE MOTION SENSOR FOR CAMERA AND DVR ACTIVATION



KEY BENEFITS

- 24.125 GHz Frequency
- Detection range = 25ft x 13ft
- IP54 protection class
- Adjustable sensitivity
- Dual voltage 13-30 VAC / 12-36 VDC
- Technology microwave and disposer
- Motion detection mode
- ABS plastic sheating

MODEL : COR-ACC-440

SPECIFICATIONS

Microwave Motion Sensor for camera and DVR activation



Thin profile design for less intrusive mounting



Motion detection from 13 to 25 feet

| | |
|-------------------------------|--|
| Detection Mode | Motion |
| Detection range | 8 * 4 meters (installation (H) 2.2m 26 * 13 feet (installation (H) 7.2 feet |
| Minimum detection speed | 5cm/s |
| Retention time | 0.5S |
| Launch frequency density | 5mW/cm2 |
| Frequency | 24 125GHz |
| Guide line | 2.5M |
| Protection class | IP54 |
| Color | Black/silvery |
| Anti-interference performance | R&TTE 1995/5/EC,EMC 89/336/EEC |
| Voltage | 2W(VA) |
| Dual voltage | 13-30 VAC / 12-36 VDC |
| Trasmitting power | 20dBm EIRP |
| Power Voltage | 12V to 30V AC+/- 10xx] 2 to+} W 12V to 36V DC |
| Maximum switching power | 30W (DC) / 60VA (AC) |
| Maximum voltage | 42AC-60V DC |
| Maximum Current | 1A |
| Working Temperature | -20° to +55° |
| Maximum Current | Maximum Current |
| Dimension | 4.72"(W) x 3.15"(H) x 1.97"(D) (120mm(W) x 80mm(H) x 50mm(D) |
| Installation Height | 4 meters (MAX) 13 feet (MAX) |
| Installation Angle | 0-90 degree (lengthways) -30 to +30 degree (lateral) |
| Weight | 104 (grams) 3.7 (ounces) |
| Certifications | CE |

