## **OUTDOOR WEATHER PROOF PROXIMITY WIEGAND READER**



The COR-ACC910 Wiegand proximity card reader is an advanced access control device in a silver-tone ABS case that uses a built-in bi-color LED to provide users with a visual indication that a card has been successfully scanned. It also has a min transducer that emits an audible "beep" when a successful operation is performed. Use the ACC900.. ACC950. ACC995 and ACC10000 CORE model access controllers for anti-pass back. It is sealed for outdoor use and has an attached cable and connector that makes installation easy and simple

| SPECIFICATIONS          |  |
|-------------------------|--|
| Card Reader Range       | 1 18cm (125kHz)  |
| Color                   | Silver-grey  |
| Request to Exit         | Supported  |
| Anti-Pass Back          | Multi-door when using COR-ACC!000  |
| Maximum # users         | 65,536 (card only) 1024 using combination of card and PIN (using attached controller or peripheral keypad) |
| Ports                   | Tamper switch, Wiegand port  |
| Wiegand ports           | W26, W34   |
| Remote operation        | Yes, using COR-ACC1000 controller  |
| Network / Communication | WG 26 / 34, ABA-II, ASYNC  |
| Baud rate               | 9600 bps (N,.8,1)  |
| Data format             | RS232  |
| Operating temperature   | -20°C to +75°C (-4°F to + 167° <b>F</b> )  |
| Placement               | Indoor or outdoor (sealed construction)  |
| Input voltage           | 9 - 16 VDC   |
| Indicators              | Bi-color LED (Red/Green),one beeper  |
| Power requirement       | ~70mA  |
| Construction            | ABS plastic  |
| Dimensions              | 81mm (L) 43mm (W) 18mm (H)<br>3.19 inches (L) 1.69 inches (W) .41 inches (H)                               |
| Weight                  | 40g (+/1 5g)   |



Z-Bracket for COR-ACC150 Maglock

COR-ACC3Z

Indoor Card Reader &



Glass Door U-Bracket for



COR-ACC3U

Sensor



COR-ACC440

Red Push-to-



COR-400II

