16 CH REAL-TIME STANDALONE NVR







	DIGITA
,	SPECIFICATIONS
* DEVICE	
Codec	H.264 (Main Profile/High Profile)
Recording Performance	480 FPS @ 1920*1080p
Playback Performance	480 FPS @ 1920*1080p
* HARDWARE	
Video Input Format	IP Camera (ONVIF® Support)
Video Input	16 CH
Video Output	1 HDMI (Max. 1920 x 1080P), 1 VGA
Audio Input	None
Audio Output	None
Audio Codec	None
Ethernet	1 Port (10 / 100 Mbps / 1 Gbps Ethernet (RJ-45))
Protocol	TCP/IP, HTTP, DHCP, ADSL(PPPoE)
PTZ Port	1 Port (RS-485 Terminal Block)
POS / ATM	3 Port (usb to serial)
Alarm In / Out	4 (NC/NO) / 1 (Relay)
USB Port	3 Ports (2 x Front Panel, 1 x Rear Panel)
Storage	Up to 2 HDD
ODD	None
* SOFTWARE	Hono
Wizard Support	Wizard for easy set up
ANS Support	Auto Network Setup Support
Record Scheduling	Fully Programmable (by Weekday / by Hour / by
	Camera / by Continous+ Event + PreEvent)
Network	Dual Stream (User Selectable)
Recording Quality	Best / High / Moderate / Economic
Scheduling Mode	Continuous / Alarm / Motion / Panic (Fully Programmable)
Pre-Event	Up to 30 minutes
Motion Detection	Region Selection (Mouse dragging support)
Playback Speed	x1, x2, x4, x8, x16, x32, x64, x128
Backup Format	EXE (Self Executable Format), JPEG
Backup Devices	CD/DVD-RW / USB
NTP	Yes
Menu	User Friendly GUI
Day Light Saving	Yes
Multi Language	33 Languages
DDNS	Bulit-in ddns / dyndns / no-ip / zoneedit / freedns
Panic Recording	Yes
CMS	Full Featured Enterprise Edition for Windows / Mac / Linux
Mobile Viewer	iPhone / Android / iPad
Operating System	Embedded Linux
* POWER	
Operating Temperature	41°F~104°F / 5°C~40°C
Operating Humidity	0% ~ 90%
Power Consumption	MAX 60W
Power	Adaptor
* PHYSICAL	, rank of
Dimensions (W x D x H)	17.32" x 3.46" x 16.15" / 440 x 88 x 410.4 mm
Weight	12 pounds / 5.44 kg (without HDD)
3	,

KEY BENEFITS

- Network Duel Streaming
- 480FPS Realtime at full HD
- ANS (Auto Network Setting)
- 256 CH Expandable full function CMS
- Next Generation Zoom
- POS / ATM Enterprise Edition
- Feature rich smart Phone APP
- 16 CH Synchoronized Simutaneous Playback

Maximize on performance with the new NV series network video recorders. Providing ample processing power for an IP camera environment and allowing quick access to video reproduction and multi-channel stream. The NV ties into the Hybix category allowing a complete hybrid environment without sacrificing the user experience. Hybix NV utilizes the latest in open compatibility compliance.



FRONT VIEW



BACK VIEW





Designed with expandability in mind, the HYBIX series will also integrate with NVR and IP products for a complete solution. Coming soon!

