## 16 CHANNEL 4K AHD | TVI / CVI | 960H | H.265 DVR | PLUS IP | 2 SATA HDD



















## SPECIFICATIONS

*RECORDING BANDWIDTH*		
IP Cam Inputs	64~192Mbps, IP Bandwidth default is 64Mbps, Decrease one Analog channel can increase 8Mbps Analog channel and digital channel can be converted	
IP Cam Out	192Mbps	
Analog Video-Input	16CH inputs	
*LIVE*		
IP Video Input	8ch (only IP up to 24ch)	
Composite Video Input	Up to 24ch (Analog Video + IP Video)	
*MONITORS*		
BNC	1 (704*576)	
VGA	1 (1024*768, 1280*720, 1280*1024,1440*900, 1920*1080)	
HDMI	1(1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 , 2560*1440, 3840*2160 / EDID)	
USB	USB 2.0*1(front) , USB 3.0*1+(rear)	
Audio	16 in /1 out	
HDD	2 SATA HDD, up to 10TB for each disk	
Ethernet	1 RJ45 100/1000 Base-T	
RS485	1	
Alarm Input /Out	16 in /1 out	
*UI / MONITORING*		
Local	UI5.0	
WEB	IE10/11,Safari V12.1 above,Firefox V.52 above,Google chrome V.57 above,Edge V.79 above	
Mobile viewer	Rxcamview	
Push Notification	Yes	
Pass Word Reset	Factory Reset : Press 10 seconds	
*RECORDING AND PLAYBACK*		
Compression	Audio: G.711a Video : H.264/H.265	
Display Resolution	Analog AHD: 8MP(15fps) 5MP(20fps) 4MP/1080P/720P/960H (30fps)	

IP: 4K/4MP/1080P/720P Single IP channel preview up to 4K 30 fps

## **KEY FEATURES**

- 4K Hybrid DVR
- H.265 / H.264 Video Compression
- All Channel Audio Inputs
- Continuous / Manual / Motion recording modes
- 4K COAX compatible and 4K HDMI output
- 2 SATA HDD, up to 10TB for each disk

The Cortex Medallion Series Hybrid 4K DVRs provide the best user experience for a fantastic value. Its the ideal solution for commercial or residential projects that combine legacy and future proof technologies. By engineering a DVR that provides durable, long lasting performance, Cortex has raised the bar for video surveillance once again. These models are a perfect fit for every install and give the owner 4K CCTV capability plus IP expansion.











## **CORTEX IQ**

*RECORDING AND PLAYBACK*	
Speed	SMain-stream
Al	PID - Perimeter Intrusion Detection,LCD - Line Crossing Detection,PD&VD - Human&Vehicle Detection, FD - Face Detection,FR - Face Recognition
Event	MD (Sensitivity Level 1~8), Video loss, Beep, Email, Push notification to Mobile APP
Playback Function	Fast forward / backward (2x, 4x, 8x,16x), Slow forward (1/2x, 1/4x, 1/8x,1/16x)
Playback	8MP:144fps (Max 16CH playback) 5MP: 240fps(Max 16CH playback) 4MP: 320fps (Max 16CH playback) 1080P:480fps (Max 16CH playback)
*GENERAL*	
OSD Language	English/French/Spanish/Portuguese/German/Italian/ Greek/Danish/Finnish/Russia/Hebrew/Turkish/Bulgarian/ Arabic/Korean/Japanese/Thai/Hindi/Romanian/ Dutch/Polish
Power Supply	DC 12V / 5A
Power consumption (excluding hard disk)	≤20W
Working Temperature	0°C~+40°C (32°F ~ 104°F)
Working Humidity	Less than 90% RH
Dimension ( W x D x H )	378 x 340 x 50mm 14.8 x 13.3 x 2 inches

