





KEY FEATURES

- 4k AHD DVR
- All Channel Audio Inputs
- H.265 / H.264 Video Compression
- Continuous / Manual / Motion recording mode
- 1SATA HDD, up to 8TB storage
- 8CH BNC inputs + 4 CH IP (via network) 12 CH total

The Cortex Medallion Series Hybrid 4K DVRs provide the best user experience for a fantastic value. Its the ideal solution for commercial or residential projects that combine legacy and future proof technologies. By engineering a DVR that provides durable, long lasting performance, Cortex has raised the bar for video surveillance once again. These models are a perfect fit for every install and give the owner 4K CCTV capability plus IP expansion.

SPECIFICATIONS

| | |
|---|---|
| Video Compression | H.265 / H.264 |
| Video System | NTSC / PAL |
| Operation System | Linux (embedded) |
| Analog video-input /out | 8CH inputs / VGA and HDMI output |
| IP Video Input | 4ch only IP |
| Composite Video Input | 8ch 960H / AHD / TVI / CVI |
| Audio input /output | 8CH inputs / 1CH output (RCA) |
| *DISPLAY* | |
| Resolution | 4K Model: Analog : 8MP(15fps) 5MP(20fps) 4MP/3MP/1080P/720P/ 960H (30fps) IP : 4MP/3MP/1080P/720P 5MP Model: Analog : 5MP(20fps) 4MP/3MP/(30fps) 1080P/ 720P / 960H IP : 4MP/3MP/1080P/720P |
| Feature | 1 / 4 / 6 / 8 / 9 / S.E.Q. |
| *RECORD* | |
| Resolution | Analog :8MP/5MP/4MP/3MP/1080P/ 720P/960H IP : 4MP/3MP/1080P/720P |
| Speed | 4K Model: Analog : 8MP:7fps(each ch) 5MP:10fps(each ch) 4MP:15fps(each ch) 3MP:17fps(each ch) 1080P:PAL:25fps(each ch)/ NTSC:30fps(each ch) IP : PAL:25fps(each ch)/NTSC: 30fps(each ch) |
| IP-Recording Bandwidth (Maximum input Bandwidth) | 32-96Mbps (decreasing one Analog channel can increase 8Mbps) |



CORTEX IQ

| | |
|-------------------------|---|
| Recording Mode | Continuous / Manual / Motion detection |
| Synchronous Playback | 8CH |
| Network Type | Lan - DHCP / and DDNS |
| HDD interface | 1SATA HDD, up to 8TB |
| Multiplex Operation | live display - record - playback - backup and network |
| USB | 1xUSB3.0 1*USB2.0(for mouse and backup / upgrade) |
| Sensor and Alarm I/Q | 8CH inputs /1CH output |
| PTZ Control | Yes (RS485) |
| Mobile Surveillance | Support IOS on iPhone and Android operation system |
| VGA / HDMI | 1024*768 / 1280*720 / 1280*1024 / 1440*900 / 1920*1080(1080P) / 2560*1440(2K) / 3840*2160(4K) |
| Power Supply | DC 12V/2A |
| Dimension (W x D x H) | 300 x 227 x 53mm 11.6 x 8.93 x 2 inches |
| Working Temperature | -10°C~+55°C |
| Working Humidity | 10%~90% |

