

# COR-ACC995V2

## BIOMETRIC FINGERPRINT, CARD READER W/ KEYPAD



The COR-ACC995V2 is perfect for high security location like police departments, casinos, banks, research facilities and storage areas that contain valuable equipment or irreplaceable property. By requiring a fingerprint in addition to a primary identification method an unauthorized intrusion is impossible under any normal circumstance.

- UP TO 9000 USERS
- LOG UP TO 32,000 EVENTS
- ADVANCED HIGH SPEED RECOGNITION
- CONTROLLER INSIDE / DIRECT CONNECT

### SPECIFICATIONS

|                       |  |
|-----------------------|--|
| Construction          | ABS & PC   |
| Mechanism             | Optical  |
| Card Reader Range     | 1.9 - 5.9 inches (5cm to 15cm)   |
| Frequency             | 125kHz proximity card operation  |
| Time zones            | 11 programmable  |
| Event log             | 32,000 events  |
| # Users               | 4500 (2 fingerprints) to 9000 (1 fingerprint)                              |
| Holiday scheduling    | User defined in client software  |
| Serial port           | No   |
| TTL Out               | Alarm, Duress, Arming LED, WG lock relay, Security trigger signal          |
| Relay output          | 1 alarm relay output, 1 lock relay output                                  |
| Anti-Tamper           | Tamper resistant switch (limit switch Form C)                              |
| Anti-Pass Back        | Multi-door when using COR-ACC1000 controller                               |
| DO                    | Door output and alarm output   |
| Door relay time       | 0 .0.1-600 sec.  |
| Alarm relay time      | 0 .0.1-600 sec.  |
| Baud rate             | 9600 bps (N,.8,1)  |
| Auxiliary WG port     | WG26, WG34   |
| Serial out            | TTL (4800 bps, N, 8, 1 )   |
| Communication         | RS-485, TCP/IP connection  |
| Digital input         | 1 Egress / RTE or 2 door contact   |
| Real time clock       | YES  |
| Power                 | 10-24VDC (<5W)   |
| Weatherproof          | NO -- indoor only  |
| Operating temperature | 0°C to +50°C (32°F to + 122° F)  |
| Indicators            | Acoustic beeper, LCD display panel, six (6) LEDs                           |
| Placement             | Indoor   |
| Dimensions            | 151mm (T) 81mm (D) 73mm (W)<br>5.9inches (T) 3.2 inches (D) 2.9 inches (W) |
| Weight                | 11.6 oz (330g)   |



COR-ACC995V2

