

COR-HTBS

VIDEO TRANSMITTER & RECEIVER W/ 4in EXTENTION CORD



This passive pair balun with built in surge protector offers a convenient and cost effective solution to transmitting video signal over 2 wire conductor (we recommend CAT5E/CAT6 twisted pair). The COR-HTBS has a 4" pigtail which allows you to connect cameras to the DVR without space restraints. Boosts video signals up to 1300ft (depending on cable quality and video signal) without power. Works with analog and analog high definition signals.

SPECIFICATIONS

BNC	Better quality zinc alloy with built-in ESD	
Crosstalk & Noise immunity	60dB	
Power Input	Passive: no power required	
Power Consumpton	Passive: no power required	
Video formats	NTSC, PAL, and SECAM	
Max.Transmission distance (Each unit)	up to 300-400m (depending on cable quality and type)	
Compatibility	HD-AHD	Yes
	HD-CVI	Yes
	HD-TVI	Yes
Connectors	(Each unit)	1 Male BNC
	(Each unit)	1 Press-Fit"terminal blocks
Terminal	100ohms	
Surge protection	4KV	
Impedance	BNC: 75ohms	
E S D	8 K V	
Attenuation	0.5dB type	
Frequency response	DC to 60Mhz	
Storage Temperature	-10°C - +70°C	
Working Temperature	-30°C - +70°C	
Humidity	0 - 90%	
Case	ABS Plastic	
Weigh	100g	
Dimensions	33mm 17mm 19mm (excluding connectors)	
	1.2 inches .66 inches .74 inches (excluding connectors)	
Press-fit terminal	Convenience for installation	
CAT-5, CAT-6 or 2 conductor	CAT-5, CAT-6 or 2 conductor	

