



KEY FEATURES

- 2.43 megapixel sensor
- Dual output: AHD and analog OSD
- 2.8-12mm varifocal megapixels rated lens
- 3D-DNR - digital wide dynamic range
- Intuitive OSD menu
- Digital De-fog
- Industrial surveillance

This super bullet outdoor camera uses advanced video processing functions that lift traditional CCTV video technology to a new level. This product provides the user with crystal clear video images that can be modified from a standard analog signal to an analog high definition signal with a simple touch of the OSD joystick.

SPECIFICATIONS

Video Sensor	1/3" 2.4 Megapixel sensor
Lens	2.8mm - 12mm Megapixel Rated Varifocal
Resolution	Digital: 1920x1080P Analog: 960H - 1200TVL
IR range	90-120 feet /27-37 meters
IR LED	60IR
Video Output	AHD: 1080P / 960P BNC CVBS: 1.0 Vp-p Composite Signal (75 Ω)
Electronic Shutter	AUTO/ MANUAL /FLK
Scanning System	Progressive Scan
Minimum Illumination	0.2 LUX (Color/Day) 0.01 LUX (B/W)
3D-DNR	OFF / ON (LOW/MIDDLE/HIGH)
Digital WDR	OFF / ON (Level Adjustable) (Long and short exposure)
OSD	Yes
Sens-Up	OFF / ON
White Balance	AWB/ ATW / PUSH / MANUAL
Back Light Control	OFF / ON
D-ZOOM	1.0x - 8.0x
TV System	NTSC
Defog	OFF / ON
Power Consumption	600mA
Working Temperature	-10° ~ to 50°C / -14° +122 °F
Power	12V DC
Dimension(D) (H)	7.87 " x 4.72 " (inches) / 200 x 120 (mm)
Weight	1.32 (lb) / 0.6 (kg)

ADDITIONAL OSD OPTIONS:

MIRROR-FLIP - DZOOM - SCALE - FORMAT - DIGITAL OUT
SHADING-PRIVACY MASK -TITLE - GAMMA

Tamperproof lens
adjustment systemUse OSD joystick to
switch between HD and
standard analog output

- Improved heavy gauge cable harness
- Heavy tamperproof bracket
- IR cut filter
- No glare, focus shift prevention
- Tamperproof lens adjustment system
- 6 Point quality control system