



## KEY FEATURES

- 1/3" 2.43 megapixel sensor
- Dual output: AHD and analog OSD
- 3.6mm megapixel rated lens
- Smart noise reduction
- Integrated lens separator
- Digital De-fog
- Industrial surveillance

## SPECIFICATIONS

Video Sensor	1/3" 2.4 Megapixel sensor
Resolution	Digital: 1920x1080P Analog: 960H
Lens	3.6mm Fixed
Illumination Range	0.1 LUX (0.0 LUX with IR on)
Video Output	AHD / BNC (selectable from OSD)
White Balance	AATW, AWC, INDOOR, OUTDOOR, MANUAL, AWB
IR Range	30-50 feet / 9-15 meters
IR LED Array	24 IR LEDS
Shutter	AES (OSD Control)
Defog	On/Off
Gain Control	AGC (OSD Control)
Scanning System	Progressive Scan
Wide Dynamic Range	Yes, with Low/Middle/High & Off (OSD Control)
Dynamic Noise Reduction	2DNR, 3DNR
BLC & HLC	Yes (OSD Control)
Image Control	Sharpness, brightness, color control (OSD Control)
Privacy Mask	4 zone (OSD Control)
Day / Night	Adjustable (OSD Control)
Weatherproof Rating	IP66 (indoor/outdoor)
Vandal Resistance	Hardened case, cable feed-through
Power	12VDC 250mA (sold separately)
Dimension (inches)	4.1"(H) x 3.67"(W) (104mm x 93.2mm)
Weight	0.53 (lbs) 240(g)

## Additional OSD Options:

Exposure-wb-manual-special-cam-title-motion-privacy-  
park-line-image-adj-comm-adj-language-area-state-  
height-width-mirror-front-contrast-sharpness

The COR-HF97E outdoor infrared bullet is designed for extremely high performance and reliability. The heavy duty aluminum-alloy base provides a cable feed-through path that protects the video and power cables from being vandalized. A cable access notch is provided in installation cases when wall access is impossible and must be flush mounted.

- Vandal resistant all metal housing
- Cable feed through bracket
- Highlight- backlight compensation
- Advanced OSD menu
- Automatic gain control



Use OSD joystick to switch between HD and standard analog output