

COR-IP2BM

2MP MINI NETWORK CAMERA



FEATURES

- 1/2.7" Progressive CMOS
- 3.6 mm IR Lens approx. 88° H.FOV
- Premium Starlight Technology
- PoE | IEEE 802.3af / IEEE 802.3at
- IR Range up to 82 feet
- Metal Housing IP66 Waterproof
- 1920(H)×1080(V) Resolution

SPECIFICATIONS

Resolution	2MP 1920(H)×1080(V)
Image Sensor	1/2.7" progressive CMOS
Min.Illumination	Color 0.01lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON
Shutter	Auto/Manual 1/5 ~ 1/20000s
Slow Shutter	Supported
Lens	3.6 mm H.FOV: 88°
Day & Night	Auto switching infrared-cut filter (OSD on/off)
WDR	Digital WDR
Video Compression	H.265 / H.264
Video Bit Rate	256Kbps ~ 8Mbps
Video Streaming	Multiple adjustable streams
Frame Rate	Mainstream up to 20fps 1080P(1920x1080), 960P(1280x960), 720P(1280x720)
Image Settings	Flip mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
BLC	Supported
ROI	Supported
Privacy Mask	Supported
Video Analytics	N/A
Protocols	TCP/IP,IPv4v6,HTTP,DHCP,DNS,DDNS, RTP/RTSP,PPPoE,SMTP,NTP,UPnP,SNMP, HTTPS,FTP



Compatibility	ONVIF®, API, Cortex Plug&Play
Interface	RJ45 10M / 100M Ethernet interface
Illumination	18pcs (SMD) Distributed Angle Stealth Cover
IR Range	Up to 82 feet (25m)
SD Storage	N/A
Alarm Trigger	N/A
Audio	N/A
Video Output	N/A
Reset System	Software
PoE	Yes, IEEE 802.3af / IEEE 802.3at
Casing	IP66
Power Supply	DC 12V / POE
Consumption	≤ 6W
Storage Temperature	-30~+60°C (-22~+140°F)
Operating Temperature	-30~+55°C (-22~+131°F)
Dimensions	Ø67 X 55mm (Ø2.6 X 2.2 inches)
Weight	Approximately .49 lbs (225g)

COR-IP2BM

