

COR-IP5DV

5MP VARIFOCAL NETWORK DOME CAMERA



FEATURES

- 1/2.9" Sony® Exmor Progressive CMOS
- 2.8 ~ 12 mm (Motorized) IR Lens
- Premium Components
- Active Shutter Controls
- IR Range up to 100 feet
- Metal Housing IP66 Waterproof
- 1920(H)×1080(V) Resolution

SPECIFICATIONS



AI Analytics	Cross line Detection, Intrusion Detection, Stationary Object Alert, Pedestrian Detection, Face Detection, Cross Counting
Protocols	TCP/IP, IPv4v6, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
Compatibility	ONVIF®, API, Cortex Plug&Play
Network Interface	RJ45 10M / 100M Ethernet interface
Illumination	40pcs(SMD)
IR Range	Up to 100 feet (30m)
ePTZ	Digital Pan Tilt Zoom
SD storage	Yes, Micro SD
Alarm Trigger	Yes, Screw Terminal
Audio	Yes
Video Output	Yes
Reset System	Hardware reset button and software
PoE	Yes, IEEE 802.3af / IEEE 802.3at
Casing	Metal Housing IP66 Waterproof
Power Supply	DC 12V / POE
Storage Temperature	-30~+60°C (-22~+140°F)
Operating Temperature	-30~+55°C (-22~+131°F)
Dimensions	Ø147 X 117mm (Ø5.78 X 4.6 inches)
Weight	Approximately 2.35 lbs (1067g)

Resolution	5MP 2592(H)×1944(V)
Image Sensor	1/2.9" Sony® Exmor Progressive CMOS (6.82M Pixels)
Min. Illumination	Color 0.01lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON
Shutter Time	Auto/Manual 1/5 ~ 1/20000s
Shutter Controls	Active Shutter Controls
Lens	2.8 ~12mm (Motorized) H.FOV: 87 ~ 28°
F-Stop	F 1.6 ~ 2.9 ±5%
Day & Night	Auto switching infrared-cut filter (OSD on/off)
WDR	Digital
Video Compression	H.265 / H.264
Video Bit Rate	8Kbps ~ 8Mbps
Video Streaming	3 individually adjustable streams
Frame Rate	Mainstream 5MP(2592×1944), 4MP(2592×1520) 3MP(2048×1520), 1080P(1920×1080), 960P(1280×960), 720P(1280×720) Substream 720P(1280×720), VGA(640×480), QVGA(320×240) Mobilestream VGA(640×480), QVGA(320×240)
Image Settings	Image rotate, Saturation, Contrast, Hue, Brightness, Sharpness
BLC	Supported
ROI	Supported
Privacy Mask	Supported

COR-IP5DV

