

MAX-260

DUAL MOUNTING (OPTION) BULLET CAMERA w/ IR



KEY FEATURES

- 420-LINE RESOLUTION
- 11 INFARED LEDs
- DUAL MOUNTING OPTIONS
- AVAILABLE IN BLACK AND BEIGE



Includes adjustable metal bracket



Beige
Model 265

SPECIFICATIONS

Horizontal resolution: 420 lines
Effective pixels: NTSC - 512 x 492 (251k) PAL - 512 x 582 (297k)
Video sensor: 1/4" CCD with digital signal processing (DSP)
Scanning system: 2:1
Minimum illumination: 0.8 LUX
Optics: 3.6mm coated precision fixed focus lens
Sync.: Internal
Signal-to-noise ratio: >48dB
Gain control: Auto-gain control (AGC)
White balance: Auto-white balance (AWB)
Auto Electronic shutter: 1/60- to 1/10,000-second
Infrared source: 11 units IR LEDs operating at 850nm
Infrared switching: Automatic, photo-sensor control
Dimensions - 1.75" wide x 2.13" tall (less with light shield removed) x 3.75" long
Power: 12VDC @ 150A (nominal)
Output: 1Vp-p composite video output @ 75 ohms
Operating Temperature: -5°~50°C (23°~122°F)
Housing: monded acrylic available in black and beige
Bracket: ball-in-socket, 360° adjustable



Removable sun/light shield

REMOVABLE SUN/LIGHT SHIELD



Attached power and video cable

MAX-260

