Compatible with BIX/NUBIX HD





SF	\sim 1		C 1	TI		VIC.
ОГ	. I	ГΙ	\smile \vdash	١I	OI	VO

* GENERAL					
Performance	Pentaplex				
Display speed	Real time				
Record speed	NTSC: 240fps @ 960H / PAL: 200fps @ 960H				
Video In /Analog Camera Loop Out	16 / 16(BNC)				
Video Out /display	1 HDMI, 1 VGA				
Video Out /resolution	1920x1080, 1600x1200, 1440x900, 1280x1024, 1280x720, 1024x968				
Video Out /Spot (CVBS)	1 BNC				
Audio/ Input / Output	8/1				
Sensor Alarm Input / Output	8/2				
* DETAILS					
Screen/ Display split	1, 4, 7, 9, 10, 13, 16				
Screen /interface	Graphic User Interface				
Video/Codec	H.264				
Video/Image quality	Highest / High / Normal / Low				
Video/Recording type	Schedule / Normal / Event (Motion, Sensor, Videoloss)				
Storage/Internal	2 HDDs x 4TB (1 HDD + DVD-RW)				
Storage/Option	Add SATA Board: 3 HDDs or 2 HDDs + DVD-RW				
Connectors/ USB / RS-485	2 USB ports / PTZ camera, PTZ controller interface				
* FUNCTIONS					
Camera option	Color adjustment/Position change / Freeze / 4X digital zoom (live/playback)				
Motion/Sensitivity	5 levels motion detection				
Motion/Area	Adjustable GRID (22 x 15)				
System/Hidden Camera	Hidden camera on live monitoring				
System/PTZ	Various PTZ camera protocol / Preset up to 255 / RS-485				
System/Private Zone	Blocking the private zone (live / playback)				
System/Auto Time Sync	NTP (Network Time Protocol)				
System/Firmware Update	USB				
System/S.M.A.R.T.	Auto detect when HDD's problem				
Event/Type	Motion / Sensor / Video loss				
Event/Action	Recording, E-Mail, Log, Send message to remote, Buzzer, Popup, Alarm, PTZ preset				
Event/Pre/Post Recording	Up to 60sec / 100sec				
Backup/ File format	DVR format				
Backup/ Media	DVD / USB device / Network				
Network/Type	Static IP / DHCP / DDNS				
Network/Base-T	10/100/1000 Mbps				
Network/Browser	CMS, Web viewer (Windows/MAC OS), Smart phone support (iPhone, iPad, Android)				

KEY FEATURES

- 16 CHANNEL 960H H.264 DVR
- **CMS PROGRAM**
- REAL HD RESOLUTION SUPPORT (HDMI PORT)
- 2 HDDs x 4TB (1 HDD + DVD-RW or eSATA)
- 1 SPOT MONITOR OUTPUT
- VERSATILE PLAYBACK FUNCTIONS
- **GIGABIT LAN**
- WINDOWS AND MAC PC COMPATIBLE WEB VIEWE
- SMARTPHONE VIEWER (IPHONE, IPAD, ANDROID)
- 480 FPS REAL TIME 960H (960 X 480) **RECORDING & PLAYBACK**
- DUAL MODE OPERATION / SMART SEARCH / SECTION REPEAT PLAYBACK

FRONT VIEW



* SEARCH /PLAYBACK					
Speed	5 steps				
Quick / Event search	Real time				
Record speed	Search by designated time / Search by event				
Section repeat playback	Playback repeating designated time section only				
Panorama search	Searching each frame in a screen simultaneously				
SMART search	SMART search				
Dual mode function	Live monitoring during playback				
* POWER					
Operating Temperature	0~45°C, 32~113°F				
Humidity	5~85%				
Power requirement	DC 12V 5A				
* PHYSICAL (WITHOUT HDD)					
Dimensions (W x H x D)	440(W) x 430(D) x 90(H) (mm) 17.3(W) x 16.9(D) x 3.5(H (inches)				
Weight	7 (kg) 15.4 (pounds)				