

MAX-GRPRO4

960H 4 CHANNEL DVR w/ REAL TIME RECORDING



SPECIFICATIONS

| | |
|----------------------------|---|
| * DISPLAY | |
| Speed | Real time with H264 Video compression |
| Display Frame Rate | Real Time 240 images per second (IPS) |
| Operating Resolution | 8CIF Record /8/8-ch playback 8HD1 Record / 1ch playback 2D1 + 6CIF record / 1 ch playback |
| Compression | Latest H264, VBR/CBR |
| Playback Split mode | View 1 camera or split screen to 4 equal sectors to view multiple channels with audio |
| High Definition VGA output | 1280 x 768, (60 IPS) 1280 x 720 (60 IPS) 1280 x 1024 (60 IPS) 1280 x 720 (60 IPS) 1366 x 768(60 IPS) 1440 x 900 (60 IPS) |
| * RECORDING | |
| Max Recording Rate | D1 Real Time 240 images per second (IPS) |
| Record Resolution (NTSC) | CIR 240 IPS (360 x 240) HD1 120 (720 x 240) D1 60IPS (720 x 480) |
| Compression | Latest H264 , VBR / CBR |
| Recording Modes | Power On auto Record /Manual / Schedule /Motion/ Sensor |
| * PLAYBACK | |
| Playback Resolution (NTSC) | CIR 240 IPS (360 x 240) HD1 120 (720 x 240) D1 60IPS (720 x 480) |
| Search | Calendar Search, Event Search, Text-In Search, Go to Time |
| Camera on Screen | View 1 camera or split screen to 4 equal sectors to view multiple channels with audio |
| Video Backup Portability | View video files in MPEG4 or AVI format on any PC |
| * VIDEO AND AUDIO | |
| Video Format | NTSC / PAL |
| Video Search Functions | time, alarm even, motion detection event list |
| Video Input | 4 Channels (BNC connectors) |
| Video Output | 1 composite , 1 VGA |
| Audio Input | 1 Channel |
| Audio Output | 1 (mono) |
| Audio Compression | ADPCM Mono |
| * DEVICE | |
| Interface | USB 2.0 for portable HDD / Flash Drive / DVD Burner and for Firmware Upgrade (when available) |
| Mobile Surveillance | 3G and 3.5G (iPhone , Blackberry, Windows Mobile, Symbian compatible) |
| User Manual | Infrared Remote control and USB Mouse Included |
| * NETWORK | |
| Interface | RJ45 10M/100M Ethernet Auto Detect |
| Protocol | TCP/IP, PPPOE, DHCP, DDNS, EMAIL |
| Remote Operation | View or Operate using client software , IE Browser (Windows 200, XP , Vista, and Windows 7 |
| *PAN TILT ZOOM | |
| PTZ Support | Supports two RS485 communication with Pelco D/P, Samsung, Panasonic protocols |

KEY FEATURES

- MOBILE DEVICE SUPPORT 3G / 3.5G
- PENTAPLEX MULTIPLE TASK OPERATION
- REMOTE SURVEILLANCE
- 4 CHANNEL RECORDING MODES
- INFRARED REMOTE CONTROL
- EASY NETWORK CONNECTION
- AUDIO SUPPORT
- MULTIPLE PTZ PROTOCOLS SUPPORTED
- VIDEO SEARCH MODES
- FULL SDK FILE SUPPORT

3G AND 3.5G
COMPATIBLE



IR REMOTE
INCLUDED



FRONT VIEW



REAR VIEW

| | |
|-------------------------------|---|
| * STORAGE & BACKUP | |
| Storage | HDD Interface up to two SATA HDDS (2T each) max. |
| Backup | External HDD(USB), External USB memory. |
| * POWER | |
| Operating Temperature | 10°C ~ 60°C / 50°F~110°F |
| Power | 12V,DC (included) 6W-230W depending on HDDs |
| * PHYSICAL | |
| Color | Black / reflective front panel |
| Dimensions (W x H x D) | 340 x 67 x 267 (mm) 13.39 x 2.64 x 10.43 (inches) |
| Weight | 2 (kg) 4.4 (pounds) (without HDD,ODD) |
| Control | Front Panel Button, USB Mouse, Remote control |

MAX-GRPRO4

