

17" **TVI 1080P** **AHD 1080P/720P** **ANALOG 960H**



### KEY BENEFITS

- 32 CH 960H/ TVI / AHD VIDEO INPUT
- PLAYBACK : 16 CH SIMULTANEOUSLY PLAYBACK
- MULTI-USER ONLINE SIMULTANEOUSLY
- HDMI 1080P OUTPUT, TRUE HIGH RESOLUTION
- DUAL STREAM TECHNOLOGY
- SMART SEARCH
- SUPPORT PTZ PRESET 255 PRESETS & 8 CRUISES

MAX-PLEX32HF series are standard 32 CH 1080P high definition DVRs, which adopt the standard H.264 high profile compression format and the most advanced SOC technique to ensure recording in each channel and realize outstanding robustness of the system.

MAX-PLEX32HF support 32 CH video input, 4 CH audio input, simultaneous 16 CH playback. The series of product can meet different security requirements of home, financial, commerce, enterprise, transportation and government, etc.

### SPECIFICATIONS

<b>* SYSTEM</b>	
Compression	Standard H.264 High Profile
CPU	Cortex A9
OS	Embedded Linx
<b>* VIDEO</b>	
Input	BNC × 32
Resolution	960H / TVI / AHD 1080P, 720P, WD1 real time
Output	HDMI × 1 : 1920 × 1080, VGA × 1 : 1920 × 1080, BNC × 1 : CVBS ( used as the main or spot output )
<b>* AUDIO</b>	
Input	RCA × 4
Output	RCA × 1
Two-way audio	Take up channel one audio input
<b>* RECORD</b>	
Resolution	1080P, 1080P lite, 720P, WD1
Frame Rate	1080P : 12 fps (PAL) / 15 fps (NTSC) 1080P lite / 720P / WD1 : 25 fps (PAL) / 30 fps (NTSC)
Record Mode	Manual, timer, motion, sensor
Bit Rate1	768Kbps ~ 8Mbps
Mode	Manual, timer, motion, sensor
<b>* PLAYBACK</b>	
Playback	16 CH
Search	Time slice / time / event / tag search
Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
Function	Play, pause, FF, FB, digital zoom, etc
<b>* ALARM</b>	
Input	4
Output	1
Triggering	Record, snap, preset, e-mail, etc.
<b>* NETWORK</b>	
Interface	RJ45 10M / 100M / 1000Mbps × 1
Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP
Web Client	Multiple users online
<b>* MOBILE DEVICES</b>	
OS	iOS, Andriod
<b>* STORAGE</b>	
HDD	SATA × 4, max 6T per HDD
<b>* BACKUP</b>	
Local Backup	U disk, USB removable HDD
Network Backup	Yes
<b>* PORT</b>	
RS485	RS485 × 1, connect to PTZ or keyboard
USB	USB 2.0 × 1 ( front panel ), USB 3.0 × 1 ( rear panel )
Remote Controller	Optional
<b>* OTHER</b>	
Power Supply	ATX 250W
Consumption	< 20W ( without HDD )
Dimensions (inches)	17" × 15" × 2.75 ( W × D × H )
Work Environment	- 10 °C ~ 50 °C / 10 % ~ 90 % Humidity



FRONT VIEW



BACK VIEW



IR Remote Control



USB Mouse



Free CMS software

